

FLEX HARROW

CONVENTIONAL TILLAGE

MODELS: FH6424HD | FH6630HD | FH6636HD | FH6642HD | FH6845HD | FH6848HD | FH6851HD

When it comes to busting clods, the Great Plains Heavy-Duty Flex Harrow is the toughest finishing tool on the market! Known for strength and simplicity, it utilizes a ladder-frame full-length tongue and a height-adjustable hitch. Flex Harrow's center frame is made entirely of ¼" wall steel, making it perfect for nearly any terrain, and the wings are constructed of 6" square tubing with reinforced corners.

For longer life and wear, the machine features 1½" pivot pins on the main pivot and wing corners. Extra large cylinders with single valve control provide lifting and folding power. Automatic cable lift means there's no need to get off the tractor to adjust. Non-puncture aircraft tires on the wings ensure longer stability and reliability. The Flex Harrow is available in widths from 24'-51' with an optional 8-, 12-, or 16-bar harrow.



FEATURES & BENEFITS

- **8-, 12-, and 16-Bar Tine Models Available in 4-Bar Sections** - Choose the option ideal for specific field conditions and desired finish. Bar sections can be added or removed.
- **Single Hydraulic Circuit** - Unit can be lifted and folded with one SCV control. Allows for unit to be pulled behind other tillage implements.
- **1½" Wing Pivot Pins** - Greasable wing pivot pins last longer and require less maintenance than competitors.
- **Heavy-Duty Frame** - Designed to handle even the toughest soil conditions, the Great Plains Flex Harrow's center frame is constructed of quarter-inch-wall steel, while its wing frames are built from 6" square tubing.
- **8-Bolt Main Transport Hubs and Non-Puncture Aircraft Tires on Wings** - With heavy-built hubs, tires are designed to run longer in tougher conditions without skipping a beat.



STANDARD EQUIPMENT

- Hydraulic wing fold
- Heavy-duty frame
- Oversized cylinders for lifting and folding
- LED safety lighting

OPTIONAL EQUIPMENT

- 8-, 12-, or 16-bar harrow



Flex Harrow	FH6424HD	FH6630HD	FH6636HD	FH6642HD	FH6845HD	FH6848HD	FH6851HD
Recommended Use	Seedbed Preparation						
Tillage Width	24'	30'	36'	42'	45'	48'	51'
Transport Width	12' 8"	12' 8"	12' 8"	12' 8"	12' 8"	12' 8"	12' 8"
Transport Height	10' 10"	10' 10"	10' 10"	10' 10"	10' 10"	10' 10"	10' 10"
H.P. Requirements	70+	90+	110+	125+	135+	145+	155+
Weight (lbs)*	4,050 - 4,550	5,000 - 5,650	6,000 - 6,450	6,200 - 6,700	6,250 - 7,250	6,700 - 7,700	7,100 - 8,300

Specifications are subject to change without prior notification. Images may or may not depict current production models.

*Approximate maximum weights with attachments