

# NEW 30' Model YIELD-PRO®

## STACK-FOLD PLANTERS

NEW!



The introduction of the 3P3025AH brings a new level of accuracy and simplicity to the mounted stack-fold planter line. Individual hoppers on each row, positive 3-section ground drive, and the proven accuracy of the Great Plains 25 Series Opener coupled with the Air-Pro® Metering System make this planter a simple, highly-productive machine.

With the option of single- or Twin-Row technology, the 3P3025AH stands in a class of its own, bringing all of the ruggedness and accuracy of our 3PYPA central-fill planter to the operator who is cost conscious, yet wants to be sure the planter has the ability to precisely space the seed, place the seed at the desired depth, firm it in the seed trench, and close the seed trench to support maximum yields.



Great Plains Ag



@GreatPlains\_Ag



Great Plains Ag

[www.GreatPlainsAg.com](http://www.GreatPlainsAg.com)

  
**Great Plains**  
"Harvest Starts Here."

# Features & Benefits

- **25 Series Row Unit** - The 25 Series Row Unit utilizes ductile cast parallel arms for long-term row unit stability. 15", 4mm blades turning on 205 triple-lip seal bearings ensure long life and accurate seed placement. Blades are offset ½" to slice residue and form a perfect seed trench.
- **Air-Pro® Meter** - This simple, positive air meter offers excellent singulation of a large number of seeds by "dead"-dropping seed directly into the Clear-Shot® seed tube.
- **3-Section Flexibility** - Planter flexes in three sections for unmatched terrain-following capabilities.
- **Multiple Row Spacings Available** - To match diverse needs, models are available in single- or twin-row configurations. Twin-row and 15" units have 1.6 bu. hoppers, and 20" to 40" single-row units have 3.0 bu. hoppers.

## Type:

Stack-Fold Planter

## Availability:

Currently available



## Standard Equipment:

- DICKEY-john® PM 400 Monitor
- Air-Pro® Meter System
- 3-section ground drive
- 25 Series Openers
  - 4mm blades
  - 205 triple-lip seal bearings
  - Heavy-duty down pressure springs
  - Cast blade separator with fertilizer tube
  - Clear-Shot® Seed Tubes
- 1.6 bu./row hopper (Twin Row and 15"); 3 bu./row hopper on wider single-row configurations
- Hydraulic lift-assist system (Standard on TR30", 15", and 20")

## Optional Equipment:

- Wing lock
- Wing flex
- Air design inside disc scrapers
- Unit-mounted coulters w/ fluted or turbo blades
- Hydraulic lift assist (optional on 30" and 22")

MODEL INFO	30' STACK-FOLD PLANTER										
MODELS	3P3025AH										
	-24TR30	-1230	-2315	-1820	-1622	-16TR36	-0836	-16TR38	-0838	-16TR40	-0840
WORKING WIDTH	30'	30'	28' 9"	30'	29' 4"	24'	24'	25' 4"	25' 4"	26' 8"	26' 8"
TRANSPORT WIDTH	15' 2"	14' 11"	16' 4"	16' 4"	15' 7"	12' 1"	12' 1"	12' 1"	12' 1"	12' 10"	12' 4"
TRANSPORT HEIGHT	12' 9"										
H.P. REQUIREMENTS	240+	180+	220+	200+	190+	190+	150+	190+	150+	190+	150+
TYPICAL WEIGHT - EMPTY	14,595 lbs	10,566 lbs	13,260 lbs	12,468 lbs	11,728 lbs	14,595 lbs	11,395 lbs	11,075 lbs	9,299 lbs	11,075 lbs	9,299 lbs
NUMBER OF OPENERS	24	12	23	18	16	16	8	16	8	16	8
ROW SPACING	Twin-Row 30"	30"	15"	20"	22"	Twin-Row 36"	36"	Twin-Row 38"	38"	Twin-Row 40"	40"
SEED CAPACITY	1.6 bu. per row (Twin Row and 15"); 3 bu. per row on wider single-row configurations										
LIFT ASSIST AVAILABLE	Standard	Optional	Standard	Standard	Optional	N/A	N/A	N/A	N/A	N/A	N/A
LIFT ASSIST TIRES	380/55R 16.5						N/A				
GAUGE WHEEL TIRES	7.60x15 6-ply Lug										

Specifications are subject to change without prior notification.